



MINING CUPLA

Safety Mining Cuplas ~ Ideal for dusty environments

SAFETY LOCK ON 600SF WILL NOT DISCONNECT ACCIDENTLY.
STAINLESS STEEL BALLS AND SPRINGS.
600PF HAS INBUILT PURGE MECHANISM.
HOSE DOESN'T WHIP WHEN DISCONNECTED.

ALL CHROME PLATED STEEL

MIN600SF-SG-SL

SAFETY LOCK SOCKET



Model	Application
MIN600SF-SG-SL	3/4"

MIN600PF-PV

PURGE PLUG



Model	Application
MIN600PF-PV	3/4"

MIN400PM

AIR CUPLA



Model	Application
MIN400PM	1/2"

Specifications

Body Material	Steel (chrome-plated)	
Size	3/4" BSP Female Thread	
Working Pressure	215 PSI	1.5MPa (15 kgf/cm ²)
Pressure Resistance	285 PSI	2.0MPa (20 kgf/cm ²)
Maximum Temperature	80°C	
Minimum Temperature	-20°C	

Specifications

Body Material	Steel (chrome-plated)	
Size	3/4" BSP Female Thread	
Working Pressure	215 PSI	1.5MPa (15 kgf/cm ²)
Pressure Resistance	285 PSI	2.0MPa (20 kgf/cm ²)
Maximum Temperature	80°C	
Minimum Temperature	-20°C	

Specifications

Body Material	Steel (chrome-plated)	
Size	1/2" BSP Male Thread	
Working Pressure	215 PSI	1.5MPa (15 kgf/cm ²)
Pressure Resistance	285 PSI	2.0MPa (20 kgf/cm ²)
Maximum Temperature	80°C	
Minimum Temperature	-20°C	

SAFETY CUPLAS

Beware of Imitations

Genuine ~ INSIST ON
NITTO CUPLA™

